

Video Decoder

**4K HDMI IP Video Decoder****NVD-40**

|                               |                                                                                                                                                                                                                                                                                                                |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Audio/Video Input             | Stream Input:<br>RTSP over UDP (Unicast / Multicast)<br>RTSP over TCP<br>RTSP over HTTP<br>SRT (Secure Reliable Transport) caller<br>MPEG-TS over UDP<br>RTMP Pull<br>RTMP Push (Internal Server)<br>UDP raw (Unicast/Multicast)<br>HLS over HTTP<br>MPEG-TS over TCP Pull<br>Supported video sharing websites |
| Audio Output                  | 2 x RCA(L/R)<br>HDMI embedded audio                                                                                                                                                                                                                                                                            |
| Video Output                  | HDMI 2.0 x 1 (Digital)<br>Composite x 1 (Analogue)                                                                                                                                                                                                                                                             |
| Network Feature               | 1x RJ-45 Female (10/100/1000M Ethernet) DHCP/Static IP                                                                                                                                                                                                                                                         |
| Supported Video Resolution    | 3840x2160p: 60/59.94/50/30/29.97/25/24/23.98 (H.265 Only)<br>1080p: 60/59.94/50/30/29.97/25/24/23.98<br>1080i: 60/59.94/50, 720p: 60/59.94/50<br>576i 50 (PAL)<br>480i 60 (NTSC)                                                                                                                               |
| Supported Decoding Resolution | Up to 2160p60/50                                                                                                                                                                                                                                                                                               |
| Control                       | Web browser UI for configuration and control<br>Socket commands                                                                                                                                                                                                                                                |
| Update                        | Automatic firmware upgrade                                                                                                                                                                                                                                                                                     |
| Power                         | Input AC 100~240V Switching Adaptor<br>Output DC 12V / 1A                                                                                                                                                                                                                                                      |
| Environmental Conditions      | Operating temperature: 0~40°C, Storage temperature: -20~60°C                                                                                                                                                                                                                                                   |
| Dimension (LxWxH)             | 220 x 143 x 42 mm                                                                                                                                                                                                                                                                                              |
| Weight                        | 1 kg                                                                                                                                                                                                                                                                                                           |
| Power                         | DC 12V, 1A                                                                                                                                                                                                                                                                                                     |
| What's in the Box             | 1 x NVD-40 product<br>1 x AD Switch DC 12V<br>1 x Remote Control                                                                                                                                                                                                                                               |